

Region:		Aosta Valley						Archetype code:			
Building category:Residential bPeriod of construction:1982 - 1991Climatic zone:E-F		Residential b	Residential buildings - Apartments (in multifamily blocks)						RES_APPBLOCK_1982-		
		1982 - 1991	1					1991_E-F_VAL			
				Number	of records:	1540					
Descript	<b>tion</b> (the codes asso	ciated with wall	s and slabs re	fer to the struct	ures descri	bed in UNI/TR	11552:2014):	Data s	ources:		
vith the	<u>l walls</u> : hollow brie ermal insulation (c <u>bs</u> : reinforced cor	od. MCV04).		·	MCV02) o	or solid brick	masonry	EPC databa	ases (100%)		
	Data		Symbol	Unit of measure	Mean value	Standard deviation	Q1 (first quartile)	Median value	Q3 (third quartile)		
	Number of floor	rs	nf	-	-	-	-	-	-		
	Gross height		Hg	m	-	-	-	-	-		
	Footprint area		A <sub>footprint</sub>	m²	-	-	-	-	-		
	Heated gross floor area		A <sub>H;g</sub>	m²	-	-	-	-	-		
ткү	Heated net floor area		A <sub>H;n</sub>	m <sup>2</sup>	-	-	-	_	-		
Ξ	Heated gross volume		V <sub>H;g</sub>	m <sup>3</sup>	-	-	_	_	-		
BUILDING GEOMETRY	Heated net volume		V <sub>H;n</sub>	m <sup>3</sup>	-	-	-	_	-		
0	Compactness ra	-	A <sub>env</sub> /V <sub>H;g</sub>	m <sup>-1</sup>	0.68	0.23	0.52	0.70	0.82		
NIC	WWR – North o		WWR <sub>N</sub>	_	0.12	0.05	0.09	0.12	0.14		
II	WWR – South o		WWRs	-	0.12	0.05	0.09	0.12	0.14		
8	WWR – East orientation		WWR <sub>E</sub>	_	0.12	0.05	0.09	0.12	0.14		
	WWR – West orientation		WWRw	_	0.12	0.05	0.09	0.12	0.14		
	Window to useful floor area		A <sub>wi</sub> /A <sub>use</sub>	-	0.12	0.06	0.12	0.12	0.19		
	Roof type					-					
	U-value of the r	oof **	U <sub>fl;up</sub>	W/(m²⋅K)	1.21	0.39	1.05	1.32	1.42		
ENVELOPE	External walls ty	/pe	Hollow brick masonry: 60%; Solid Brick masonry: 30%; Masonry with local stones: 4%; Concrete wa 3%; Unknown: 3%								
	U-value of the v	vall	U <sub>wl</sub>	W/(m²⋅K)	0.86	0.40	0.55	0.82	1.10		
/EL	Slab on ground	floor type				-					
EN	U-value of the f	oor **	U <sub>fl;lw</sub>	W/(m²⋅K)	1.03	0.26	0.93	1.11	1.18		
	Windows type		Double glazing, wooden frame: 85%; Double glazing, PVC frame: 9%; Single glazing, wooden 4%; Triple glazing, wooden frame: 1%; Triple glazing, PVC frame: 1%								
	U-value of the v	vindows	Uw	W/(m²⋅K)	2.60	0.73	2.35	2.70	2.90		
	Shading system	type				-					
_ Z	Occupancy dens	cupancy density *		Oc person/m² UNI EN 16798-1 - Table A.19							
anc	Lighting power density *		W <sub>L</sub>	W/m <sup>2</sup>	UNI EN 16798-1 - A.8.3						
ILA N	Equipment pow	er density *	W <sub>A</sub>	W/m <sup>2</sup> UNI EN 16798-1 - A.8.3							
GAINS and VENTILATION	Type of ventilat	ion				Natural:	100%				
>	Air exchange ra	te *	n	h-1	0.30	0.00	0.30	0.30	0.30		
	Heating system	type			Centr	alized: 55%; A	utonomous: 45%	%			
S	Heating generat	or	Boiler (unknown type): 41%; Traditional Boiler: 28%; Condensing Boiler: 12%; Heat exchanger of district heating/cooling: 10%; Fireplace: 5%; Unknown: 3%; Air-source heat pump: 1%								
	Daily operating heating system		t <sub>H</sub>	h			-				
N	Energy carrier	rgy carrier Gas Oil: 50%; Natural Gas: 17%; LPG: 16%; Solid biomass: 14%; District heating: 4%									
ιsγ	Heating emissio	Heating emission sub-system -									
THERMAL SYSTEMS	Cooling system type					Absent:	100%				
	Daily operating cooling system		tc	h	-	-	-	-	-		
	Cooling emissio	n sub-system				-					
	DHW system ty		Autonomous, detached from heating: 46%; Autonomous, coupled with heating: 28%; Centralized, coupled with heating: 25%; Centralized, detached from heating: 1%								
	DHW generator	Unknown: 56%; Natural gas boiler: 24%; Electric boiler: 19%; Electric Heat Pump: 1%									







Region:	Archetype code:			
Building category:	Residential buildings - A	RES_APPBLOCK_1982-		
Period of construction: 1982 - 1991				1991_E-F_VAL
Climatic zone:	E-F	Number of records:	1540	

ADDITIONAL DATA								
	Data	Symbol	Unit of measure	Mean value	Standard deviation	Q1 (first quartile)	Median value	Q3 (third quartile)
GEOMETRY: apartments	Inter-storey height	H <sub>n</sub>	m	2.6	0.3	2.4	2.5	2.7
	Heated gross floor area	A <sub>H;g</sub>	m <sup>2</sup>	-	-	-	-	-
	Heated net floor area	A <sub>H;n</sub>	m <sup>2</sup>	62.2	32.3	39.6	54.9	76.9
	Heated gross volume	V <sub>H;g</sub>	m <sup>3</sup>	226.4	122.0	143.9	197.9	279.3
0.6	Heated net volume	V <sub>H;n</sub>	m <sup>3</sup>	159.6	86.9	101.0	140.4	199.2
THERMAL SYSTEMS	Heating efficiency or COP	$\eta_{ extsf{H}; extsf{gen}}$ or $ extsf{COP}_{ extsf{H}; extsf{gen}}$	-	This value has to be retrieved from suitable datasheets			tasheets	
	Total heating power *	P <sub>H;gen</sub>	kW	22.4	9.2	15.0	24.0	30.0
	Cooling efficiency or EER	η <sub>C;gen</sub> or EER <sub>C;gen</sub>	-	This value has to be retrieved from suitable datasheets			tasheets	
	Total cooling power *	P <sub>C;gen</sub>	kW	4.6	2.1	3.5	3.8	4.9
	Temperature of DHW	ϑ <sub>w</sub>	°C	40.0	0.0	40.0	40.0	40.0
É	DHW system power *	P <sub>W;gen</sub>	kW	11.6	12.4	1.2	2.0	24.0
	* These values refer to the apartment scale							

## Additional data: GEOMETRY (the plots refer to the apartment scale)





