

| Region: | | Trentino | | Archetype code: | | | | | | |
|---|---|--|--|--|---------|-----------|----------------------|---------------|-----------|--|
| Building category: | | Catering bu | ildings | CATR_ | | | | | | |
| | | 1931-1940 | | 1931-19 | 40_F_TN | | | | | |
| Climatic zone: F | | Number of records: 7 | | | | | | | | |
| Description (the codes associated with wa | | alls and slabs | refer to the stru | Data s | ources: | | | | | |
| External walls: no data available | | | | | | | EPC databases (100%) | | | |
| <u>Roof sla</u> | <u>bs</u> : no data availa | able | | | | | | | | |
| | | | | | | | | | | |
| | Data | | Symbol | Unit of | Mean | Standard | Q1 (first | Median | Q3 (third | |
| | | | | measure | value | deviation | quartile) | value | quartile) | |
| | Number of floors | | n _f | - | - | - | - | - | - | |
| | Gross height | | Hg | m | - | - | - | - | - | |
| | Footprint area | | A _{footprint} | m² | - | - | - | - | - | |
| ≻ | Heated gross floor area | | A _{H;g} | m² | - | - | - | - | - | |
| BUILDING GEOMETRY | Heated net floor area | | A _{H;n} | m² | 115 | 61 | 76 | 101 | 134 | |
| | Heated gross volume | | V _{H;g} | m ³ | - | - | - | - | - | |
| | Heated net volume | | V _{H;n} | m ³ | 477 | 217 | 325 | 411 | 583 | |
| | Compactness ratio | | A _{env} /V _{H;g} | m ⁻¹ | 0.64 | 0.18 | 0.46 | 0.66 | 0.76 | |
| | WWR – North orientation | | WWR _N | - | - | - | - | - | - | |
| | WWR – South orientation | | WWRs | - | - | - | - | - | - | |
| | WWR – East orientation | | WWR _E | - | - | - | - | - | - | |
| | | WWR – West orientation | | - | - | - | - | - | - | |
| | Window to useful floor | | A _{wi} /A _{use} | - | - | - | - | - | - | |
| | area ratio | | | | | - | | | | |
| | Roof type U-value of the r | raaf | 11- | W/(m²·K) | _ | - | _ | _ | _ | |
| ų | External walls t | | U _{fl;up} | vv/(III-'K) | - | - | - | - | - | |
| | U-value of the v | / . | U _{wl} | W/(m²·K) | _ | - | _ | _ | - | |
| | Slab on ground | | Uwi | vv /(iii ix) | | - | | | | |
| ENVELOPE | U-value of the f | | U _{fl;lw} | W/(m ² ·K) | _ | - | - | _ | - | |
| Ē | Windows type | | | ••• | | - | | | | |
| | | U-value of the windows | | W/(m²·K) | - | - | _ | - | - | |
| | Shading system type | | Uw | ,(| | - | | | | |
| | Occupancy density * | | Oc | O _C person/m ² UNI EN 16798-1 - Table A.19 | | | | | | |
| P NO | Lighting power density * | | W _L | W/m ² | | | INI EN 16798-1 | - A.8.3 | | |
| S an ATI | Equipment pow | · · · | | | | | | | | |
| GAINS and ENTILATIOI | * | | W _A | W/m ² | - A.8.3 | | | | | |
| GAINS al VENTILATI | Type of ventilat | Type of ventilation | | Natural: 100% | | | | | | |
| | Air exchange rate * | | n h ⁻¹ UNI EN 16798-1 | | | | | | | |
| | Heating system type | | Unknown 72%; %Centralized: 14%; Autonomous: 14%; | | | | | | | |
| | Heating generator | | Boiler (unknown type): 86%; Unknown: 14% | | | | | | | |
| | Daily operating | | tн | h | | | No limitatio | n | | |
| ٨S | heating system * | | | | | | | | | |
| | Energy carrier | | Natural gas: 33%; LPG: 33%; Gas oil: 17%, Solid biomass: 17% | | | | | | | |
| TEN | Heating emission sub- | | - | | | | | | | |
| THERMAL SYSTEMS | system Cooling system type | | Unknown: 100% | | | | | | | |
| | Daily operating time of the | | | | | | | | | |
| | cooling system * | | t _c | h | | | No limitatio | n | | |
| Ξ | | Cooling emission sub- | | | | - | | | | |
| | system | | | | | | | | | |
| | DHW system ty | ре | Autonomous – coupled with heating: 43%; Autonomous - detached fr coupled with heating: 14%; Unknown: 14 | | | | • | centralized – | | |
| | DHW generator | DHW generator Natural gas boiler: 34%; Electric Heat Pump: 33%; Electric boiler: 33% | | | | | | | | |
| | * These values were not available in the considered sources, and are thus derived from UNI EN Standards | | | | | | | | | |



The data can be used for analysis, modeling, and research purposes, as long as it remains unaltered in its original form. Users are free to publish results based on the data, provided they credit the original source. Catering buildings – 1931/1940 – Zone F – Trentino 1





€ () _ () original form. Users are free to publish results based on the data, provided they credit the original source. Catering buildings – 1931/1940 – Zone F – Trentino

2



| Region: | Trentino | Archetype code: | | |
|-------------------------|--------------------|----------------------|--|--|
| Building category: | Catering buildings | CATR_ | | |
| Period of construction: | 1931-1940 | 1931-1940_F_TN | | |
| Climatic zone: | F | Number of records: 7 | | |

| ADDITIONAL DATA | | | | | | | | |
|-----------------|--|---|--------------------|---|--------------------|------------------------|-----------------|------------------------|
| | Data | Symbol | Unit of measure | Mean value | Standard deviation | Q1 (first quartile) | Median value | Q3 (third quartile) |
| THERMAL SYSTEMS | Heating efficiency or COP | η _{H;gen} or COP _{H;gen} | - | This value has to be retrieved from suitable datasheets | | | | |
| | Total heating power * | P _{H;gen} | kW | 27 | 12 | 18 | 26 | 32 |
| | Cooling efficiency or EER $\eta_{C;gen}$ or EER C;gen-This value has to be retrieved from suitable datashe | | | | | | asheets | |
| | Total cooling power * | P _{C;gen} | kW | - | - | - | - | - |
| | Temperature of DHW | ϑw | °C | 40 | - | 40 | 40 | 40 |
| | DHW system power * | P _{W;gen} | kW | 22 | 14 | 14 | 26 | 32 |







