

Region:		Trentino		Archetype code:						
Building category:		Catering bu	ildings	CATR_						
		1951-1960			1951-19	60_F_TN				
Climatic zone: F		Number of records: 64								
Description (the codes associated with wa		alls and slabs	refer to the stru			1552:2014):	Data s	ources:		
External walls: no data available Roof slabs: no data available				EPC databases (100%)						
Data		Symbol	Unit of	Mean	Standard	Q1 (first	Median	Q3 (third		
				measure	value	deviation	quartile)	value	quartile)	
	Number of floors		n _f	-	-	-	-	-	-	
	Gross height		Hg	m	-	-	-	-	-	
	Footprint area		A _{footprint}	m ²	-	-	-	-	-	
RY	Heated gross floor area		A _{H;g}	m ²		-	-	-	-	
BUILDING GEOMETRY	Heated net floor area		A _{H;n}	m ² m ³	194	217	88	120	201	
	Heated gross volume		V _{H;g}	m ³	-	-	-	-	-	
	Heated net volume		V _{H;n} A _{env} /V _{H;g}	m ⁻¹	775	852	354	502	797	
	· ·	Compactness ratio			0.69	0.17	0.59	0.68	0.78	
		WR – North orientation		-	-	-	-	-	-	
	WWR – South c		WWRs WWR _E	-	-	-	-	-	-	
		WR – East orientation		-	-	-	-	-	-	
			WWR _W	-	-	-	-	-	-	
	area ratio	Window to useful floor area ratio		-	-	-	-	-	-	
	Roof type									
		<i>U</i> -value of the roof		W/(m²⋅K)	-	-	-	-	-	
	External walls t		U _{fl;up}	,,,,,		-				
ΒE	U-value of the v	vall	U _{wl}	W/(m²⋅K)	-	-	-	-	-	
ENVELOPE	Slab on ground	floor type				-				
N	U-value of the f	loor	U _{fl;lw}	W/(m²·K)	-	-	-	-	-	
	Windows type	/indows type				-				
	U-value of the v	U-value of the windows		W/(m²·K)	-	-	-	-	-	
	Shading system type					-				
	Occupancy density *		Oc	<i>O</i> _C person/m ² UNI EN 16798-1 - Table A.19						
PN	Lighting power	density *	WL	W/m ²	UNI EN 16798-1 - A.8.3					
GAINS and VENTILATIOI	Equipment power density		WA	W/m²	UNI EN 16798-1 - A.8.3					
NEN G	Type of ventilation		Natural: 100%							
	Air exchange rate *		n h ⁻¹ UNI EN 16798-1							
	Heating system type		Unknown 47%; Autonomous: 34%; Centralized: 19%							
	Heating generator		Boiler (unknown type): 91%; Unknown: 5%; Air-source heat pump: 2%; Fireplace: 2%							
THERMAL SYSTEMS	Daily operating time of the heating system *		t _H h No limitation							
	Energy carrier		Natural gas: 46%, Gas oil: 30%; Solid biomass: 13%; LPG: 9%; Electricity: 2%							
	Heating emission sub- system		-							
	Cooling system type		Unknown: 95%; Air-cooled chiller: 5%							
	Daily operating time of the cooling system *		t _C h No limitation							
	Cooling emission sub- system		-							
	DHW system ty	ре	Autonomous – coupled with heating: 42%; Unknown: 27%; Autonomous - detached from heating: 19% Centralized – coupled with heating: 9%; District heating:3%						n heating: 19%;	
	DHW generator	IW generator Natural gas boiler: 63%; Electric Heat Pump:19%; Unknown 9%; Electric boiler: 9%								
	* These values were not available in the considered sources, and are thus derived from UNI EN Standards									



The data can be used for analysis, modeling, and research purposes, as long as it remains unaltered in its original form. Users are free to publish results based on the data, provided they credit the original source. Catering buildings – 1951/1960 – Zone F – Trentino 1





€ () _ ()

The data can be used for analysis, modeling, and research purposes, as long as it remains unaltered in its original form. Users are free to publish results based on the data, provided they credit the original source. Catering buildings – 1951/1960 – Zone F – Trentino 2



Region:	Trentino	Archetype code:	
Building category:	Building category: Catering buildings		
Period of construction:	Period of construction: 1951-1960		
Climatic zone:	F	Number of records: 64	

ADDITIONAL DATA								
	Data	Symbol	Unit of measure	Mean value	Standard deviation	Q1 (first quartile)	Median value	Q3 (third quartile)
THERMAL SYSTEMS	Heating efficiency or COP	η _{H;gen} or COP _{H;gen}	-	This value has to be retrieved from suitable datasheets				
	Total heating power *	P _{H;gen}	kW	63	108	24	29	49
	Cooling efficiency or EER	r <i>EER</i> $\eta_{C;gen}$ or $P_{C;gen}$ - This value has to be retrieved from suitable datasheets						asheets
	Total cooling power *	P _{C;gen}	kW	17	7	13	15	18
	Temperature of DHW	ϑw	°C	40	-	40	40	40
	DHW system power *	P _{W;gen}	kW	35	38	19	26	34









