

Region: Aosta Valley Archetype code: Non-residential buildings - Educational buildings **Building category:** EDUC 1946-1981 E-F VAL **Period of construction:** 1946-1981 E-F Climatic zone: Number of records: Description (the codes associated with walls and slabs refer to the structures described in UNI/TR 11552:2014): Data sources: EPC databases (100%) External walls: hollow brick masonry with thermal insulation (cod. MCV02). Roof slabs: reinforced concrete floor slab for non-walkable flat roof (cod. COP01) or for pitched roof (cod. CIN04). **Data Symbol** Unit of Mean **Standard** Q1 (first Median Q3 (third measure value deviation quartile) value quartile) Number of floors $n_{\rm f}$ Gross height H_{g} m Footprint area m^2 $A_{\text{footprint}}$ m^2 Heated gross floor area $A_{H;g}$ **BUILDING GEOMETRY** 799.4 653.1 293.8 688.2 Heated net floor area **А**н<u>;п</u> m^2 1016.1 Heated gross volume 3502.6 2928.5 2840.0 4810.4 $V_{\rm H;g}$ m^3 1221.3 Heated net volume m^3 2176.9 1902.1 789.9 1949.3 2788.0 $V_{H;n}$ Compactness ratio $A_{\rm env}/V_{\rm H;g}$ m⁻¹ 0.56 0.14 0.45 0.52 0.62 WWR - North orientation WWR_{N} 0.15 0.05 0.12 0.14 0.17 WWR - South orientation WWR_S 0.15 0.05 0.12 0.14 0.17 WWR - East orientation 0.15 0.05 0.17 WWR_E 0.12 0.14 WWR - West orientation WWR_W 0.15 0.05 0.12 0.14 0.17 Window to useful floor area 0.17 0.04 0.15 0.17 0.20 A_{wi}/A_{use} ratio Roof type

 $W/(m^2 \cdot K)$

 $W/(m^2 \cdot K)$

h

 $U_{\mathsf{fl};\mathsf{up}}$

 U_{wl}

ENVELOPE

U-value of the roof **

External walls type

U-value of the wall

Slab on ground floor type

Daily operating time of the

Cooling emission sub-system

cooling system *

DHW system type

THERMAL SYSTEMS

<i>U</i> -value of the floor **	U _{fl;lw}	W/(m²⋅K)	1.52	0.71	1.25	1.50	2.00
Windows type	Double glazing, wooden frame: 83%; Double glazing, PVC frame: 9%; Single glazing, wooden frame: 8%						
<i>U</i> -value of the windows	U_{W}	W/(m²⋅K)	2.48	0.79	1.96	2.30	2.95
Shading system type				-			
Occupancy density *	O _C person/m ² UNI EN 16798-1 - Table A.19						
Lighting power density *	W∟	W _L W/m ² UNI EN 16798-1 - A.8.3					
Equipment power density *	W _A	W _A W/m ² UNI EN 16798-1 - A.8.3					
Type of ventilation				-			
Air exchange rate *	n	h ⁻¹	-	-	-	-	-
Heating system type	Autonomous: 100%						
Heating generator	Boiler (unknown type): 93%; Condensing Boiler: 7%						
Daily operating time of the heating system *	t _H	h			-		
Energy carrier	Gas Oil: 43%; Natural Gas: 43%; LPG: 7%; Solid biomass: 7%						
Heating emission sub-system	-						
Cooling system type	Absent: 100%						
	4						

1.02

1.08

0.77

0.63

Hollow brick masonry: 47%; Masonry with local stones: 20%; Solid Brick masonry: 20%; Concrete wall:

13%

Autonomous, detached from heating: 60%; Centralized, coupled with heating: 40%

0.59

0.57

0.70

1.21

1.78

1.44

DHW generator Unknown: 93%; Electric Heat Pump: 7% * These values are derived from UNI EN ISO Standards; ** U-values of the upper slab face the external environment, and the lower slab is in contact with the ground

 t_{C}



Region:	Aosta Valley	Archetype code:		
Building category:	Non-residential building	EDUC_1946-1981_E-F_VAL		
Period of construction:	1946-1981			
Climatic zone:	E-F	Number of records:	15	



The data can be used for analysis, modeling, and research purposes, as long as it remains unaltered in its original form. Users are free to publish results based on the data, provided they credit the original source.



 Region:
 Aosta Valley
 Archetype code:

 Building category:
 Non-residential buildings - Educational buildings
 EDUC_1946-1981_E-F_VAL

 Period of construction:
 1946-1981

 Climatic zone:
 E-F
 Number of records:
 15

ADDITIONAL DATA								
	Data	Symbol	Unit of measure	Mean value	Standard deviation	Q1 (first quartile)	Median value	Q3 (third quartile)
L SYSTEMS	Heating efficiency or COP	η _{H;gen} or COP _{H;gen}	-	This value has to be retrieved from suitable datasheets				
	Total heating power	P _{H;gen}	kW	32.4	3.0	31.1	33.0	34.0
	Cooling efficiency or EER	$\eta_{C;gen}$ or $\mathit{EER}_{C;gen}$	-	This value has to be retrieved from suitable datasheets				
MA	Total cooling power	P _{C;gen}	kW	-	-	-	-	-
THERMAL	Temperature of DHW	ϑw	°C	40.0	0.0	40.0	40.0	40.0
	DHW system power	P _{W;gen}	kW	60.0	60.8	5.1	52.0	93.8
	* This value refers to the building scale							

Numerical variables - GAINS, VENTILATION and SYSTEMS USAGE **AIR EXCHANGE RATE OCCUPACY DENSITY** 0.30 5.00 4.50 0.25 4.00 3.50 0.20 3.00 2.50 0.15 2.00 0.10 1.50 1.00 0.05 0.50 0.00 0.00 **INTERNAL GAINS POWER DENSITY DAILY OPERATING TIME** 10 14 12 8 10 7 8 6 6 5 4 3 2 2 1 \square Heating \blacksquare Cooling



Region:	Aosta Valley	Archetype code:		
Building category:	Non-residential building	EDUC_1946-1981_E-F_VAL		
Period of construction:	1946-1981			
Climatic zone:	E-F	Number of records:	15	

