

Region:
Liguria
Archetype code:

Building category:
Residential buildings – Apartments in multi-family block
Period of construction:
-1950
Climatic zone:
E
Number of records:
2177

Description: Data sources:

External walls: no data available Roof slabs: no data available

EPC databases (100%)


Number of floors Gross height Footprint area Heated gross floor area Heated net floor area Heated net volume Compactness ratio WWR – North orienta WWR – South orienta WWR – East orientati WWR – West orientati Window to useful floor ratio Roof type U-value of the roof External walls type U-value of the floor Windows type U-value of the window Shading system type Occupancy density * Lighting power densit Equipment power densit Equipment power densit Equipment power densit Type of ventilation Air exchange rate * Heating system type Heating generator Daily operating time of heating system type Daily operating time of cooling system type											
Heated gross floor area Heated net floor area Heated net volume Compactness ratio WWR – North oriental WWR – South oriental WWR – South oriental WWR – West oriental Window to useful floor ratio Roof type U-value of the roof External walls type U-value of the window Shading system type U-value of the window Shading system type U-value of ventilation Air exchange rate * Heating generator Daily operating time of heating system type Daily operating time of Cooling system type Daily operating time of		Symbol	Unit of measure	Mean value	Standard deviation	Q1 (first quartile)	Q2 (Median value)	Q3 (third quartile)			
Heated gross floor are Heated net floor area Heated gross volume Heated net volume Compactness ratio WWR – North oriental WWR – South oriental WWR – East orientati Window to useful floor ratio Roof type U-value of the roof External walls type U-value of the floor Windows type U-value of the floor Windows type U-value of the window Shading system type Occupancy density * Lighting power densit Equipment power densit		n _f	-	-	-	-	-	-			
Heated gross floor are Heated net floor area Heated net volume Compactness ratio WWR – North orienta WWR – South orienta WWR – East orientati WWR – West orientati Window to useful floor ratio Roof type U-value of the roof External walls type U-value of the floor Windows type U-value of the floor Windows type U-value of the window Shading system type Occupancy density * Lighting power densit Equipment power densit		Hg	m	-	-	-	-	-			
Heated net floor area Heated gross volume Heated net volume Compactness ratio WWR – North orienta WWR – South orienta WWR – East orientati Window to useful floor ratio Roof type U-value of the roof External walls type U-value of the wall Slab on ground floor to U-value of the floor Windows type U-value of the window Shading system type Occupancy density * Lighting power densit Equipment power densit Equipment power densit Type of ventilation Air exchange rate * Heating system type Heating system type Daily operating time of heating system type Daily operating time of the dispension sub Cooling system type Daily operating time of the dispension sub Cooling system type Daily operating time of the dispension sub		A _{footprint}	m²	-	-	-	-	-			
WWR – East orientati WWR – West orientati WWR – West orientati Window to useful floor ratio Roof type U-value of the roof External walls type U-value of the floor Windows type U-value of the window Shading system type Occupancy density * Lighting power density Equipment power density Equipment power density Type of ventilation Air exchange rate * Heating system type Heating generator Daily operating time of heating system type Cooling system type Daily operating time of the density system type	rea	A _{H;g}	m²	-	-	-	-	-			
WWR – East orientati WWR – West orientati WWR – West orientati Window to useful floor ratio Roof type U-value of the roof External walls type U-value of the floor Windows type U-value of the window shading system type Occupancy density * Lighting power density * Lighting power density * Lighting power density * Heating system type Heating system type Heating generator Daily operating time of heating system type Cooling system type Daily operating time of heating emission sub Cooling system type Daily operating time of heating emission sub	ea	A _{H;n}	m²	-	-	-	-	-			
WWR – East orientati WWR – West orientati WWR – West orientati Window to useful floor ratio Roof type U-value of the roof External walls type U-value of the floor Windows type U-value of the window shading system type Occupancy density * Lighting power density * Lighting power density * Lighting power density * Heating system type Heating system type Heating generator Daily operating time of heating system type Cooling system type Daily operating time of heating emission sub Cooling system type Daily operating time of heating emission sub	e	V _{H;g}	m³	-	-	-	-	-			
WWR – East orientati WWR – West orientati WWR – West orientati Window to useful floor ratio Roof type U-value of the roof External walls type U-value of the floor Windows type U-value of the window shading system type Occupancy density * Lighting power density * Lighting power density * Lighting power density * Heating system type Heating system type Heating generator Daily operating time of heating system type Cooling system type Daily operating time of heating emission sub Cooling system type Daily operating time of heating emission sub		V _{H;n}	m³	-	-	-	-	-			
WWR – East orientati WWR – West orientati WWR – West orientati Window to useful floor ratio Roof type U-value of the roof External walls type U-value of the wall Slab on ground floor to the window stype U-value of the window shading system type Occupancy density * Lighting power density * Lighting power density * Equipment power density * Heating system type Heating system type Heating generator Daily operating time of heating system type Heating emission sub Cooling system type Daily operating time of heating system type Daily operating time of heating system type		A _{env} /V _{H;g}	m ⁻¹	0.67	0.22	0.52	0.69	0.80			
WWR – East orientati WWR – West orientati WWR – West orientati Window to useful floor ratio Roof type U-value of the roof External walls type U-value of the floor Windows type U-value of the window shading system type Occupancy density * Lighting power density * Lighting power density * Lighting power density * Heating system type Heating system type Heating generator Daily operating time of heating system type Cooling system type Daily operating time of heating emission sub Cooling system type Daily operating time of heating emission sub	tation	WWR _N	-	-	-	-	-	-			
WWR – East orientati WWR – West orientati WWR – West orientati Window to useful floor ratio Roof type U-value of the roof External walls type U-value of the floor Windows type U-value of the window Shading system type Occupancy density * Lighting power density * Lighting power density * Lighting power density * Heating system type Heating system type Heating system type Heating system type Heating system * Energy carrier Heating emission sub Cooling system type Daily operating time of the system type	tation	WWR _S	-	-	-	-	-	-			
Window to useful floor ratio Roof type U-value of the roof External walls type U-value of the wall Slab on ground floor the window stype U-value of the window shading system type Occupancy density * Lighting power density Equipment power density Equipment power density and it is exchange rate and it is exchange rate. Heating generator Daily operating time of the window shading system type. Heating emission sub Cooling system type Daily operating time of the wall state of the window shading system type. Cooling system type Daily operating time of the wall state of	tion	WWR _E	-	-	-	-	-	-			
Roof type U-value of the roof External walls type U-value of the wall Slab on ground floor to U-value of the floor Windows type U-value of the window Shading system type Occupancy density * Lighting power densit Equipment power dentity to the company of the window Air exchange rate to the window Air exchange rate t	ation	WWR _W	-	-	-	-	-	-			
U-value of the roof External walls type U-value of the wall Slab on ground floor to U-value of the floor Windows type U-value of the window Shading system type Occupancy density * Lighting power densite Equipment power densite Equipment power densite Type of ventilation Air exchange rate * Heating system type Heating system type Daily operating time of heating system type Daily operating time of heating system type Daily operating time of heating system type	oor area	A _{wi} /A _{use}	-	0.11	0.04	0.09	0.10	0.12			
External walls type U-value of the wall Slab on ground floor to U-value of the floor Windows type U-value of the window Shading system type Occupancy density * Lighting power densit Equipment power densit Equipment power densit Type of ventilation Air exchange rate * Heating system type Heating generator Daily operating time of heating system type Heating emission sub Cooling system type Daily operating time of the window system type Daily operating time of the window system type Daily operating time of the wall U-value of the wall Slab on ground floor to the window system type U-value of the floor Windows type U-value of the wall U-value of the wall Slab on ground floor to the window system type U-value of the window system type U-value of the wall U-value of the window system type U-value of the floor type U-value of the window system type U-value of the floor type U-value of the floor type U-value of the window system type U-value of the wi					-						
U-value of the wall Slab on ground floor to U-value of the floor Windows type U-value of the window Shading system type Occupancy density * Lighting power densit Equipment power densit Equipment power densit Type of ventilation Air exchange rate * Heating system type Heating generator Daily operating time of heating system * Energy carrier Heating emission sub Cooling system type Daily operating time of		U _{fl;up}	W/(m²⋅K)	1.58	0.89	0.99	1.64	1.96			
Windows type U-value of the window Shading system type Occupancy density * Lighting power densit Equipment power der Type of ventilation Air exchange rate * Heating system type Heating generator Daily operating time of heating system * Energy carrier Heating emission sub Cooling system type Daily operating time of the system type Daily operating time of the system type					-						
Windows type U-value of the window Shading system type Occupancy density * Lighting power densit Equipment power der Type of ventilation Air exchange rate * Heating system type Heating generator Daily operating time of heating system * Energy carrier Heating emission sub Cooling system type Daily operating time of the system type Daily operating time of the system type		$U_{ m wl}$	W/(m²⋅K)	1.74	0.63	1.26	1.67	2.27			
Windows type U-value of the window Shading system type Occupancy density * Lighting power densite Equipment power densite Eq	r type				-						
Windows type U-value of the window Shading system type Occupancy density * Lighting power densite Equipment power densite Eq		U _{fl;lw}	W/(m²⋅K)	1.77	0.64	1.36	1.69	2.02			
Shading system type Occupancy density * Lighting power densit Equipment power densit Type of ventilation Air exchange rate * Heating system type Heating generator Daily operating time of heating system * Energy carrier Heating emission sub Cooling system type Daily operating time of the system type Daily operating time of the system type Daily operating time of the system type					-						
Occupancy density * Lighting power densit Equipment power densit Equipment power densit Type of ventilation Air exchange rate * Heating system type Heating generator Daily operating time of heating system * Energy carrier Heating emission sub Cooling system type Daily operating time of the system type Daily operating time of the system type	ows	U _W	W/(m²⋅K)	4.05	1.21	3.16	4.17	5.00			
Lighting power densit Equipment power densit Equipment power densit Type of ventilation Air exchange rate * Heating system type Heating generator Daily operating time of heating system * Energy carrier Heating emission sub Cooling system type Daily operating time of	2			-							
Lighting power densit Equipment power densit Equipment power densit Type of ventilation Air exchange rate * Heating system type Heating generator Daily operating time of heating system * Energy carrier Heating emission sub Cooling system type Daily operating time of	k	O _C	person/m ²		UN	II EN 16798-1	- Table A.19				
Heating system type Heating generator Daily operating time of heating system * Energy carrier Heating emission sub Cooling system type Daily operating time of	sity *	W _L	W/m²	UNI EN 16798-1 - A.8.3							
Heating system type Heating generator Daily operating time of heating system * Energy carrier Heating emission sub Cooling system type Daily operating time of		W _A	W/m²								
Heating system type Heating generator Daily operating time of heating system * Energy carrier Heating emission sub Cooling system type Daily operating time of	·			Natural: 100%							
Heating system type Heating generator Daily operating time of heating system * Energy carrier Heating emission sub Cooling system type Daily operating time of		n	h ⁻¹	0.30	0.00	0.30	0.30	0.30			
Heating generator Daily operating time of heating system * Energy carrier Heating emission sub Cooling system type Daily operating time of				Unkn	own: 96%; Au	utonomous: 4	%				
heating system * Energy carrier Heating emission sub Cooling system type Daily operating time of		Unknown: 53%; Traditional boiler: 33%; Condensing boiler: 7%; Fireplace: 6%; Air-source heat pump: 1%									
Energy carrier Heating emission sub Cooling system type Daily operating time of	of the	t _H	h	14	0	14	14	14			
Heating emission sub Cooling system type Daily operating time of		Unknown: 53%; Natural gas: 22%; Electricity and natural gas: 13%; Electricity and solid biomass: 5%; LPG: 3%; Solid biomass: 2%; Gas Oil: 1%; Electricity: 1%									
Cooling system type Daily operating time of	b-system	Unknown: 50%; Radiators: 42%; Air Ducts: 3%; Radiant panels: 2%; Convectors: 1%; Fancoil: 1%; Air Heater: 1%									
Daily operating time of	!	Unknown: 99%; Heat pump air-air: 1%									
cooling system *	of the	t _C	h	-	-	-	-	-			
Cooling emission sub-	b-system	-									
DHW system type		-									
DHW generator		Unknown: 73%; Electric boiler: 13%; Condensing boiler: 8%; Natural gas boiler: 4%; Electric heat pump: 2%									




 Region:
 Liguria
 Archetype code:


 Building category:
 Residential buildings – Apartments in multi-family block
 RES_APPBLOCK_-1950_E_LIG

 Period of construction:
 -1950
 Number of records:
 2177








OPAQUE BUILDING COMPONENTS UVALUE 3.50 3.00 2.50 1.50 1.00 0.50 0.00 External walls Slab on ground floor Roof



Numerical variables – GAINS, VENTILATION and SYSTEMS USAGE (Standard Values)









The data can be used for analysis, modeling, and research purposes, as long as it remains unaltered in its original form. Users are free to publish results based on the data, provided they credit the original source.




 Region:
 Liguria
 Archetype code:

 Building category:
 Residential buildings – Apartments in multi-family block
 RES_APPBLOCK_-1950_E_LIG

 Period of construction:
 -1950_E_LIG

 Climatic zone:
 E
 Number of records:
 2177

ADDITIONAL DATA												
	Data	Symbol	Unit of measure	Mean value	Standard deviation	Q1 (first quartile)	Median value	Q3 (third quartile)				
GEOMETRY: apartments	Inter-storey height	H_{n}	m	3.1	0.3	2.9	3.1	3.3				
	Heated gross floor area	$A_{H;g}$	m²									
	Heated net floor area	$A_{H;n}$	m²	71.8	35.6	50.0	65.2	85.0				
	Heated gross volume	$V_{H;g}$	m³	300.1	157.5	206.0	269.1	355.1				
0 10	Heated net volume	$V_{H;n}$	m³	204.4	111.3	137.1	183.3	246.8				
THERMAL SYSTEMS	Heating efficiency or COP	η _{H;gen} or <i>COP</i> _{H;gen}	-	This value has to be retrieved from suitable datasheets								
	Total heating power *	$P_{H;gen}$	kW	22.3	6.9	23.0	24.0	24.6				
	Cooling efficiency or EER	$\eta_{C;gen}$ or $\mathit{EER}_{C;gen}$	-	This value has to be retrieved from suitable datasheets								
	Total cooling power *	$P_{C;gen}$	kW	-	-	-	-	-				
	Temperature of DHW	$ heta_{\sf W}$	°C	-	-	-	-	-				
	DHW system power *	$P_{ m W;gen}$	kW	18.2	10.4	2.9	24.0	24.0				
	* These values refer to the apartment scale											







NOTE: Sample size of the analysed data.

Compactness ratio: 2165; Window to useful floor area ratio: 166; U-value of the roof: 449; U-value of the wall: 1955; U-value of the floor: 198; U-value of the windows: 2177; Inter-storey height: 2175; Heated net floor area: 2175; Heated gross volume: 2165; Heated net volume: 2165; Total heating power: 806; DHW system power: 1282; CO2 Emission: 2069; EP_H_nren: 2169; EP_W_nren: 2058; EP_GL_nren: 2161; EP_H_ren: 1238; EP_W_ren: 1187