

 Region:
 Aosta Valley (Aosta, Quart, Saint-Christophe, and Sarre)
 Archetype code:

 Building category:
 Residential buildings - Apartments (in multifamily blocks)
 RES_APPBLOCK_2006-_E_VAL

 Period of construction:
 > 2005
 _E_VAL

 Climatic zone:
 E
 Number of records:
 494

Description (the codes associated with walls and slabs refer to the structures described in UNI/TR 11552:2014):

External walls: hollow brick masonry with thermal insulation (cod. MCV02).

Roof slabs: reinforced concrete floor slab (cod. SOL04).

Data sources:

EPC databases (100%)

	Data	Symbol	Unit of	Moon	Standard	O1 /first	Median Q3 (third				
	Data	Symbol	measure	Mean value	Standard deviation	Q1 (first quartile)	value	Q3 (third guartile)			
BUILDING GEOMETRY	Number of floors	n _f	-	-	-	-	-	- quartie,			
	Gross height	Hg	m	_	-	-	-	-			
	Footprint area	A _{footprint}	m ²	_	_	-	-	-			
	Heated gross floor area	A _{H;g}	m ²	_	-	-	-	-			
	Heated net floor area	A _{H;n}	m ²	_	-	-	-	-			
	Heated gross volume	V _{H;g}	m ³	_	-	-	-	-			
	Heated net volume	V _{H;n}	m ³	_	_	_	_	_			
	Compactness ratio	A _{env} /V _{H;g}	m ⁻¹	0.62	0.24	0.41	0.64	0.79			
	WWR – North orientation	WWR _N	-	0.14	0.06	0.10	0.13	0.17			
	WWR – South orientation	WWR _S	-	0.14	0.06	0.10	0.13	0.17			
	WWR – East orientation	WWRE	-	0.14	0.06	0.10	0.13	0.17			
	WWR – West orientation	WWR _W	-	0.14	0.06	0.10	0.13	0.17			
	Window to useful floor area										
	ratio	A_{wi}/A_{use}	-	0.19	0.09	0.15	0.17	0.21			
ENVELOPE	Roof type				-						
	<i>U</i> -value of the roof **	$U_{fl;up}$	W/(m²⋅K)	0.74	0.49	0.34	0.46	1.17			
	External walls type	Hollow brick masonry: 66%; Solid Brick masonry: 27%; Unknown: 5%; Prefabricated panels: 1%; Concrete wall: 1%									
	<i>U</i> -value of the wall	U _{wl}	W/(m²·K)	0.38	0.25	0.23	0.27	0.44			
	Slab on ground floor type				-						
	<i>U</i> -value of the floor **	U _{fl;lw}	W/(m²·K)	0.43	0.27	0.27	0.35	0.42			
	Windows type	Double glazing, wooden frame: 86%; Double glazing, PVC frame: 10%; Triple glazing, PVC frame: 2%; Triple glazing, wooden frame: 2%									
	<i>U</i> -value of the windows	U _W	W/(m ² ·K)	1.75	0.66	1.31	1.56	2.03			
	Shading system type				-						
_ z	Occupancy density *	O _C	person/m²	n ² UNI EN 16798-1 - Table A.19							
GAINS and VENTILATION	Lighting power density *	W_{L}	W/m ²	UNI EN 16798-1 - A.8.3							
SN Z	Equipment power density *	W _A	W/m ²	UNI EN 16798-1 - A.8.3							
EN GA	Type of ventilation			Natural: 100%							
~ >	Air exchange rate *	n	h ⁻¹	0.30	0.00	0.30	0.30	0.30			
	Heating system type		Autonomous: 62%; Centralized: 38%								
THERMAL SYSTEMS	Heating generator	Boiler (unknown type): 32%; Condensing Boiler: 24%; Traditional Boiler: 14%; Air-source heat pump: 12%; Heat exchanger of district heating/cooling: 10%; Water-source heat pump: 4%; Unknown: 2%; Fireplace: 2%									
	Daily operating time of the heating system *	t _H	h	14.0	0.0	14.0	14.0	14.0			
	Energy carrier	Natural Gas: 73%; District heating: 10%; LPG: 8%; Solid biomass: 6%; Gas Oil: 3%									
	Heating emission sub-system	-									
	Cooling system type	Absent: 87%; Water-cooled chiller: 5%; Air-cooled chiller: 5%; Unknown: 3%									
	Daily operating time of the cooling system *	t _C	h	-	-	-	-	-			
	Cooling emission sub-system	-									
	DHW system type	Autonomous, coupled with heating: 54%; Centralized, coupled with heating: 33%; Autonomous, detached from heating: 13%									
	DHW generator	Unknown: 43%; Natural gas boiler: 36%; Electric Heat Pump: 16%; Electric boiler: 5%									
	* These values are derived from UNI EN ISO Standards; ** U-values of the upper and lower slabs face unconditioned spaces (i.e., attic, basement, etc.)										



 Region:
 Aosta Valley (Aosta, Quart, Saint-Christophe, and Sarre)
 Archetype code:

 Building category:
 Residential buildings - Apartments (in multifamily blocks)
 RES_APPBLOCK_2006-__E_VAL

 Period of construction:
 > 2005
 _E_VAL

 Climatic zone:
 E
 Number of records:
 494



The data can be used for analysis, modeling, and research purposes, as long as it remains unaltered in its original form. Users are free to publish results based on the data, provided they credit the original source.




 Region:
 Aosta Valley (Aosta, Quart, Saint-Christophe, and Sarre)
 Archetype code:

 Building category:
 Residential buildings - Apartments (in multifamily blocks)
 RES_APPBLOCK_2006-__E_VAL

 Period of construction:
 > 2005
 _E_VAL

 Climatic zone:
 E
 Number of records:
 494

ADDITIONAL DATA											
	Data	Symbol	Unit of measure	Mean value	Standard deviation	Q1 (first quartile)	Median value	Q3 (third quartile)			
GEOMETRY: apartments	Inter-storey height	H _n	m	2.7	0.2	2.6	2.6	2.7			
	Heated gross floor area	A _{H;g}	m²	-	-	-	-	-			
	Heated net floor area	A _{H;n}	m²	78.0	36.4	55.6	70.6	92.6			
	Heated gross volume	V _{H;g}	m³	309.2	155.6	211.1	269.3	375.6			
	Heated net volume	V _{H;n}	m³	185.2	92.4	128.5	171.5	214.5			
THERMAL SYSTEMS	Heating efficiency or COP	η _{H;gen} or <i>COP</i> _{H;gen}	-	This value has to be retrieved from suitable datasheets							
	Total heating power *	P _{H;gen}	kW	20.5	9.7	13.0	24.0	26.6			
	Cooling efficiency or EER	η _{C;gen} or EER _{C;gen}	-	This value has to be retrieved from suitable datasheets							
	Total cooling power *	P _{C;gen}	kW	11.7	12.0	2.3	5.2	23.9			
	Temperature of DHW	$\vartheta_{\sf W}$	°C	40.0	0.0	40.0	40.0	40.0			
Ė	DHW system power *	P _{W;gen}	kW	19.1	10.8	8.0	23.8	26.0			
	* These values refer to the apartment scale										





 Region:
 Aosta Valley (Aosta, Quart, Saint-Christophe, and Sarre)
 Archetype code:

 Building category:
 Residential buildings - Apartments (in multifamily blocks)
 RES_APPBLOCK_2006-_E_VAL

 Period of construction:
 > 2005
 LE_VAL

 Climatic zone:
 E
 Number of records:
 494

