

 Region:
 Piedmont
 Archetype code:

 Building category:
 Residential buildings - Apartments (in multifamily blocks)
 RES_APPBLOCK_2011

 Period of construction:
 > 2010
 _E_PIE

 Climatic zone:
 E
 Number of records:
 13162

Description (the codes associated with walls and slabs refer to the structures described in UNI/TR 11552:2014):

External walls: hollow brick masonry with thermal insulation (cod. MCV02).

Roof slabs: reinforced concrete floor slab (cod. SOL04).

Data sources:

EPC databases (100%)

	Data	Symbol	Unit of	Mean value	Standard deviation	Q1 (first quartile)	Median value	Q3 (third quartile)			
BUILDING GEOMETRY	Number of floors	n _f	measure	value	- ueviation	quartile)	value	quartile)			
	Gross height	Hg	m	_	_	_	_	_			
	Footprint area	A _{footprint}	m²	_	-	-	-	-			
	Heated gross floor area	A _{H;g}	 m²	_	-	-	-	-			
	Heated net floor area	A _{H;n}	 m²	_	-	-	-	-			
	Heated gross volume	V _{H;g}	m ³	-	-	-	_	-			
	Heated net volume	V _{H;n}	m ³	-	-	-	-	-			
	Compactness ratio	A _{env} /V _{H;g}	m ⁻¹	0.60	0.23	0.42	0.61	0.74			
	WWR – North orientation	WWR _N	-	-	-	-	-	-			
팅	WWR – South orientation	WWR _S	-	-	-	-	-	-			
—	WWR – East orientation	WWR _E	-	-	-	-	-	-			
	WWR – West orientation	WWR _W	-	-	-	-	-	-			
	Window to useful floor area ratio	A _{wi} /A _{use}	-	0.18	0.07	0.14	0.17	0.21			
	Roof type				-						
	<i>U</i> -value of the roof	$U_{\mathrm{fl;up}}$	W/(m ² ·K)	-	-	-	-	-			
	External walls type	Hollow	brick masonry: 7	onry: 76%; Solid Brick masonry: 19%; Unknown: 4%; Prefabricated panels: 1%							
)PE	<i>U</i> -value of the wall	U_{wl}	W/(m ² ·K)	-	-	-	-	-			
Œ	Slab on ground floor type				-						
ENVELOPE	<i>U</i> -value of the floor	U _{fl;lw}	W/(m ² ·K)	-	-	-	-	-			
	Windows type	-									
	<i>U</i> -value of the windows	U_{W}	W/(m²⋅K)	1.75	0.69	1.33	1.57	1.96			
	Shading system type		-								
_ z	Occupancy density *	<i>O</i> _C	person/m²	UNI EN 16798-1 - Table A.19							
and TIO	Lighting power density *	W_{L}	W/m ²	UNI EN 16798-1 - A.8.3							
NS E	Equipment power density *	W_{A}	W/m ²	UNI EN 16798-1 - A.8.3							
GAINS and VENTILATION	Type of ventilation			Natural: 100%							
~ >	Air exchange rate *	n	h ⁻¹	0.30	0.00	0.30	0.30	0.30			
	Heating system type	Autonomous: 57%; Centralized: 43%									
	Heating generator	-									
THERMAL SYSTEMS	Daily operating time of the heating system *	t _H	h	14.00	0.00	14.00	14.00	14.00			
	Energy carrier	Natural Gas: 80%; Electricity: 6%; District heating: 6%; Solid biomass: 4%; LPG: 2%; Gas Oil: 2%									
	Heating emission sub-system	-									
	Cooling system type				-						
	Daily operating time of the cooling system *	t _C	h	-	-	-	-	-			
	Cooling emission sub-system				-						
	DHW system type	Autonomous, coupled with heating: 47%; Centralized, coupled with heating: 32%; Autonomous, detached from heating: 13%; Centralized, detached from heating: 8%									
	DHW generator	-									
	* These values are derived from UNI EN ISO Standards										



 Region:
 Piedmont
 Archetype code:

 Building category:
 Residential buildings - Apartments (in multifamily blocks)
 RES_APPBLOCK_2011

 Period of construction:
 > 2010
 _E_PIE

 Climatic zone:
 E
 Number of records:
 13162



The data can be used for analysis, modeling, and research purposes, as long as it remains unaltered in its original form. Users are free to publish results based on the data, provided they credit the original source.




 Region:
 Piedmont
 Archetype code:

 Building category:
 Residential buildings - Apartments (in multifamily blocks)
 RES_APPBLOCK_2011

 Period of construction:
 > 2010
 _E_PIE

 Climatic zone:
 E
 Number of records:
 13162

ADDITIONAL DATA										
	Data	Symbol	Unit of measure	Mean value	Standard deviation	Q1 (first quartile)	Median value	Q3 (third quartile)		
GEOMETRY: apartments	Inter-storey height	H _n	m	-	-	-	-	-		
	Heated gross floor area	A _{H;g}	m²	-	-	-	-	-		
	Heated net floor area	A _{H;n}	m ²	85.6	46.7	57.2	75.5	101.4		
	Heated gross volume	V _{H;g}	m³	345.1	196.0	227.2	301.5	408.5		
	Heated net volume	V _{H;n}	m³	-	-	-	-	-		
THERMAL SYSTEMS	Heating efficiency or COP	η _{H;gen} or <i>COP</i> _{H;gen}	-	This value has to be retrieved from suitable datasheets						
	Total heating power *	P _{H;gen}	kW	18.0	10.1	7.7	20.6	25.0		
	Cooling efficiency or EER	η _{C;gen} or <i>EER</i> _{C;gen}	-	This value has to be retrieved from suitable datasheets						
	Total cooling power *	P _{C;gen}	kW	8.5	7.4	4.1	6.0	8.7		
	Temperature of DHW	ϑ_{W}	°C	40.0	0.0	40.0	40.0	40.0		
Ŧ	DHW system power *	$P_{\mathrm{W;gen}}$	kW	17.0	10.9	6.7	19.0	25.0		
	* These values refer to the apartment s	scale								





 Region:
 Piedmont
 Archetype code:

 Building category:
 Residential buildings - Apartments (in multifamily blocks)
 RES_APPBLOCK_2011-__E_PIE

 Period of construction:
 > 2010
 _E_PIE

 Climatic zone:
 E
 Number of records:
 13162

