

 Region:
 Piedmont
 Archetype code:

 Building category:
 Residential buildings - Single family houses
 RES_SINGLE_2001-2010_F_PIE

 Period of construction:
 2001-2010
 2010_F_PIE

 Climatic zone:
 F
 Number of records:
 298

Description (the codes associated with walls and slabs refer to the structures described in UNI/TR 11552:2014):

External walls: hollow brick masonry with thermal insulation (cod. MCV02).

<u>Roof slabs</u>: insulated reinforced concrete floor slab for walkable flat roof (cod. COP03), for pitched roof (cod. CIN03) or insulated wooden floor slab for pitched roof (cod. CIN02).

Data sources: EPC databases (100%)

| | Data | Symbol | Unit of | Mean | Standard | Q1 (first | Median | Q3 (third | |
|-------------------|--|---|--|---------------|-----------|-----------|--------------|-----------|--|
| BUILDING GEOMETRY | Number of floors | ne | measure | value | deviation | quartile) | value | quartile) | |
| | Gross height | n _f | | - | - | - | | - | |
| | Footprint area | Hg | m m ² | - | - | - | - | - | |
| | Heated gross floor area | A _{footprint} | m ² | - | - | - | <u>-</u> | - | |
| | Heated gross floor area | A _{H;g} | m ² | 137.7 | 63.8 | 95.6 | 128.0 | 169.4 | |
| | | A _{H;n} | m ³ | 532.3 | 245.6 | 361.5 | 483.8 | 666.9 | |
| | Heated gross volume Heated net volume | V _{H;g} | m ³ | 332.3 | 243.0 | - 301.3 | - 403.0 | - | |
| 5 | Compactness ratio | V _{H;n} | m ⁻¹ | 0.80 | 0.19 | 0.68 | 0.80 | 0.91 | |
| Ž | <u> </u> | A _{env} /V _{H;g} | - | | 0.19 | | - | 0.91 | |
| ╡ | WWR – North orientation | WWR _N | | - | - | - | - | - | |
| a | WWR – South orientation | WWR _S | - | - | - | - | - | - | |
| | WWR – East orientation | WWRE | - | - | - | - | - | - | |
| | WWR – West orientation | WWR _W | - | - | - | - | - | - | |
| | Window to useful floor area ratio | A _{wi} /A _{use} | - | 0.18 | 0.06 | 0.13 | 0.17 | 0.21 | |
| | Roof type | | | | - | | | | |
| | <i>U</i> -value of the roof | $U_{\mathrm{fl;up}}$ | W/(m²·K) | - | - | - | - | - | |
| | External walls type | Hollow brick masonry: 68%; Solid Brick masonry: 22%; Unknown: 9%; Prefabricated panels: 1% | | | | | | | |
| ENVELOPE | <i>U</i> -value of the wall | $U_{ m wl}$ | W/(m²·K) | - | - | - | - | - | |
| | Slab on ground floor type | | | | - | | | | |
| EN | <i>U</i> -value of the floor | $U_{fl;lw}$ | W/(m²⋅K) | - | - | - | - | - | |
| | Windows type | | | | - | | | | |
| | <i>U</i> -value of the windows | U_{W} | W/(m²⋅K) | 2.26 | 0.80 | 1.76 | 2.21 | 2.71 | |
| | Shading system type | - | | | | | | | |
| z | Occupancy density * | O _C person/m ² UNI EN 16798-1 - Table A.19 | | | | | | | |
| VENTILATION | Lighting power density * | W _L | | | | | | | |
| ₫ | Equipment power density * | W _A | W _A W/m ² UNI EN 16798-1 - A.8.3 | | | | | | |
| Ë | Type of ventilation | Natural: 100% | | | | | | | |
| > | Air exchange rate * | n | h ⁻¹ | 0.30 | 0.00 | 0.30 | 0.30 | 0.30 | |
| | Heating system type | Autonomous: 100% | | | | | | | |
| | Heating generator | | | | | | | | |
| THERMAL SYSTEMS | Daily operating time of the heating system * | t _H | h | No limitation | | | | | |
| | Energy carrier | Natural Gas: 60%; Solid biomass: 14%; Electricity: 13%; LPG: 11%; Gas Oil: 1%; Thermal energy from solar collectors: 1% | | | | | | | |
| | Heating emission sub-system | - | | | | | | | |
| | Cooling system type | | | | - | | | | |
| | Daily operating time of the cooling system * | t _C | h | - | - | - | - | - | |
| | Cooling emission sub-system | | | | | | | | |
| | DHW system type | Autonomous, coupled with heating: 86%; Autonomous, detached from heating: 12%; Centralized, coupled with heating: 2% | | | | | | | |
| | DHW generator | - | | | | | | | |



 Region:
 Piedmont
 Archetype code:

 Building category:
 Residential buildings - Single family houses
 RES_SINGLE_2001-2010 - 2010_F_PIE

 Climatic zone:
 F
 Number of records: 298



The data can be used for analysis, modeling, and research purposes, as long as it remains unaltered in its original form. Users are free to publish results based on the data, provided they credit the original source.



 Region:
 Piedmont
 Archetype code:

 Building category:
 Residential buildings - Single family houses
 RES_SINGLE_2001-2010-2010-2010-7.

 Period of construction:
 2001-2010
 2010_F_PIE

 Climatic zone:
 F
 Number of records:
 298

| ADDITIONAL DATA | | | | | | | | |
|-----------------|---------------------------|--|-----------------|---|--------------------|---------------------|-----------------|---------------------|
| | Data | Symbol | Unit of measure | Mean value | Standard deviation | Q1 (first quartile) | Median value | Q3 (third quartile) |
| THERMAL SYSTEMS | Heating efficiency or COP | $\eta_{\sf H;gen}$ or $COP_{\sf H;gen}$ | - | This value has to be retrieved from suitable datasheets | | | | |
| | Total heating power | P _{H;gen} | kW | 35.5 | 170.7 | 23.7 | 26.0 | 30.0 |
| | Cooling efficiency or EER | $\eta_{	extsf{C};	extsf{gen}}$ or $	extsf{\textit{EER}}_{	extsf{C};	extsf{gen}}$ | - | This value has to be retrieved from suitable datasheets | | | | |
| | Total cooling power | P _{C;gen} | kW | 4.3 | 1.8 | 3.5 | 3.5 | 5.5 |
| | Temperature of DHW | ϑ_{W} | °C | 40.0 | 0.0 | 40.0 | 40.0 | 40.0 |
| É | DHW system power | P _{W;gen} | kW | 24.9 | 8.2 | 23.7 | 25.8 | 29.9 |

Numerical variables - GAINS, VENTILATION and SYSTEMS USAGE **AIR EXCHANGE RATE OCCUPACY DENSITY** 0.30 5.00 4.50 0.25 4.00 3.50 0.20 3.00 2.50 0.15 2.00 0.10 1.50 1.00 0.05 0.50 0.00 0.00 **INTERNAL GAINS POWER DENSITY DAILY OPERATING TIME** 10 14 12 8 10 7 8 6 5 4 3 2 1 \square Heating \blacksquare Cooling



| Region: | Region: Piedmont | | | | |
|-------------------------|----------------------------|--------------------|-----|--|--|
| Building category: | Residential buildings - Si | RES_SINGLE_2001- | | | |
| Period of construction: | 2001-2010 | 2010_F_PIE | | | |
| Climatic zone: | F | Number of records: | 298 | | |

