

Region:		Trentino						Archetype code:			
Building category:		Residential	multifamily	RES_APPBLOCK_							
		1961-1970	`		1961-19	70_F_TN					
Climatic zone: F		F									
Descript	ion (the codes ass	ociated with w	alls and slabs	refer to the stru	ictures describ	ed in UNI/TR 1	1552:2014):	Data s	ources:		
<u>External</u>	walls: no data av	vailable						EPC databa	ases (100%)		
Roof sla	<u>bs</u> : no data availa	able									
	Data		Symbol	Unit of	Mean	Standard	Q1 (first	Median	Q3 (third		
			measure	value	deviation	quartile)	value	quartile)			
	Number of floors		nf	-	-	-	-	-	-		
	Gross height		Hg	m	-	-	-	-	-		
	Footprint area		A _{footprint}	m²	-	-	-	-	-		
≿	Heated gross floor area		A _{H;g}	m ²	-	-	-	-	-		
ETR	Heated net floor area		A _{H;n}	m ²	533	461	334	390	535		
No	Heated gross volume		V _{H;g}	m ³	-	-	-	-	-		
GEC	Heated net volume		V _{H;n}	m³	1904	1500	1253	1436	2010		
5 N	Compactness ratio		A _{env} /V _{H;g}	m ⁻¹	0.60	0.12	0.51	0.61	0.66		
BUILDING GEOMETRY	WWR – North orientation		WWR _N WWR _S	-	-	-	-	-	-		
		WWR – South orientation		-	-	-	-	-	-		
	WWR – East orientation		WWR _E	-	-	-	-	-	-		
	WWR – West o		WWRw	-	-	-	-	-	-		
	Window to user area ratio	ful floor	A _{wi} /A _{use}	-	-	-	-	-	-		
	Roof type					-					
	<i>U</i> -value of the roof		U _{fl;up}	W/(m²⋅K)	-	-	_		_		
	External walls t		Off;up	VV/(III 'K)	_	-					
H	U-value of the v		U _{wl}	W/(m²·K)	-	-	_	_	_		
ENVELOPE	Slab on ground		UWI	vv /(iii ix)		-					
Ň	<i>U</i> -value of the f		U _{fl;lw}	W/(m²·K)	-	-	_	_	-		
ш	Windows type		- 11,199	,		-					
	U-value of the windows		Uw	W/(m²⋅K)	-	-	-	-	-		
	Shading system type			,,,,,		-			I		
	Occupancy density *		Oc	person/m ²	erson/m ² UNI EN 16798-1 - Table A.19						
noi NOi	Lighting power	•	WL	W/m ²		ι	INI EN 16798-1	- A.8.3			
	Equipment pow	Equipment power density		141/m2							
GAINS and VENTILATIO	*		WA W/m² UNI EN 16798-1 - A.8.3								
ς Γ	Type of ventilation					Natural: 10	1				
	Air exchange ra	te *	n	h⁻¹	0.3	-	0.3	0.3	0.3		
	Heating system type		Centralized: 39%; Autonomous: 33%; Unknown 28%								
	Heating genera		Boiler (unknown type): 97%; Fireplace: 3%								
		operating time of the		t _H h No limitation							
THERMAL SYSTEMS	Energy carrier	neating system *		District heating: 49%; Electricity from PV, wind turbines, hydraulic turbines: 31%; Electricity: 20%							
		ing emission sub-		District nearing, 45%, Lieuthicity non riv, wind turbines, nyurduit turbines, 51%; Eleuthicity: 20%							
	system		-								
	Cooling system type		Unknown: 100%								
	Daily operating time of the										
	cooling system *		t _C h No limitation								
	Cooling emission sub-		-								
	system	system		Autonomous – coupled with heating: 37%; Centralized – coupled with heating: 24% Autonomous -							
	DHW system ty	ре	detached from heating: 17%; Unknown: 16%; District heating: 6%						atonomous -		
	DHW generator Natural gas boiler: 70%; Electric Heat Pump: 16%; Unknown 8%; Electric boiler: 5%; Solar thermal:							ar thermal: 1%			
	* These values were	e not available in	* These values were not available in the considered sources, and are thus derived from UNI EN Standards								



The data can be used for analysis, modeling, and research purposes, as long as it remains unaltered in its original form. Users are free to publish results based on the data, provided they credit the original source. Residential multifamily buildings – 1961/1970 – Zone F – Trentino





(i) (i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(i)
(

The data can be used for analysis, modeling, and research purposes, as long as it remains unaltered in its original form. Users are free to publish results based on the data, provided they credit the original source. Residential multifamily buildings – 1961/1970 – Zone F – Trentino



Region:	Archetype code: RES_APPBLOCK_			
Building category:				
Period of construction:	1961-1970_F_TN			
Climatic zone:	F	Number of records:	2723	

ADDITIONAL DATA								
	Data	Symbol	Unit of measure	Mean value	Standard deviation	Q1 (first quartile)	Median value	Q3 (third quartile)
GEOMETRY: apartments	Inter-storey height	Hn	m	-	-	-	-	-
	Heated gross floor area	A _{H;g}	m²	-	-	-	-	-
	Heated net floor area	A _{H;n}	m²	97	44	68	86	107
	Heated gross volume	V _{H;g}	m³	-	-	-	-	-
	Heated net volume	V _{H;n}	m³	363	173	251	318	410
THERMAL SYSTEMS	Heating efficiency or COP	η _{H;gen} or COP _{H;gen}	-	This value has to be retrieved from suitable datasheets				
	Total heating power *	P _{H;gen}	kW	69	106	24	30	46
	Cooling efficiency or EER	$\eta_{C;gen}$ or $FER_{C;gen}$ - This value has to be retrieved from suitable datasheets					tasheets	
	Total cooling power *	P _{C;gen}	kW	8	4	6	8	10
	Temperature of DHW	ϑ _w	°C	40	-	40	40	40
	DHW system power *	P _{W;gen}	kW	50	90	22	27	34

Additional data: GEOMETRY (the plots refer to the apartment scale) GROSS HEIGHT NUMBER OF FLOORS Ε <u>AREA</u> VOLUME \mathbf{B}_2 Gross heated volume Gross heated floor area



The data can be used for analysis, modeling, and research purposes, as long as it remains unaltered in its original form. Users are free to publish results based on the data, provided they credit the original source. Residential multifamily buildings – 1961/1970 – Zone F – Trentino



